

Email this request form to orders@noblecompany.com or fax to (231) 799-8850, and Noble Company will return a lead time and quote for approval. Manufacturing of the base will not begin until after approval and Noble Company receives the Purchase Order. Shower bases are non-refundable and non-returnable. All Noble Company terms and conditions apply.

NOBLE USE ONLY

1. CONTACT INFORMATION			Date:
Name:			
Company:			
Phone:	Email:		
Address:			
City:	State:	Zip:	

1. SHIPPING INFORMATION (if different from contact information)		
Name:		
Company:		
Phone:	Email:	
Address:		
City:	State:	Zip:

2. PROBASE II CUSTOM SHOWER BASE MATERIAL SELECTION			
<input type="checkbox"/> Honeycomb Composite Base	<input type="checkbox"/> Foam Base	<input type="checkbox"/> Pre-Waterproofed Honeycomb Composite Base	<input type="checkbox"/> Pre-Waterproofed Foam Base

For RECTANGLE or SQUARE shaped bases, use section 3a or 3b below. For UNIQUE shapes (Neo-Angle, L-Shaped, etc.) use section 3c on the reverse side of this form.

3a. PROBASE® II MULTI-SLOPE™ CUSTOM DIMENSIONS - Rectangle / Square
<input type="checkbox"/> Check this box for Multi-Slope Base
<ul style="list-style-type: none"> • Standard base thickness is 1/2" at drain; 1/8" for Clamping Ring Drains at drain • 1/4"-per-foot slope to drain • Base thickness is uniform at perimeter of base • Center of drain cannot be less than 10 inches from the edge of the base

3b. PROBASE® II SINGLE-SLOPE CUSTOM DIMENSIONS - Rectangle / Square
<input type="checkbox"/> Check this box for Single-Slope Base
<ul style="list-style-type: none"> • Standard base thickness is either 1/4" or 3/8" at drain; refer to section 4b • Slope is 1/4"-per-foot from drain to furthest edge • Standard Single-Slope bases include a 4 1/2" shim to space drain from wall • If drain ordered is less than width of base, a shim will be included to center drain

4a. DRAIN HOLE STYLE FOR MULTI-SLOPE
<input type="checkbox"/> FreeStyle Thin-Bed Drain™
<input type="checkbox"/> Bonding Flange Drain
<input type="checkbox"/> Clamping Ring Drain (includes NobleFlex Drain Flashing)

4b. DRAIN BEING USED FOR SINGLE-SLOPE	
<input type="checkbox"/> FreeStyle Linear Drain™ Drain Body Sitting on Substrate 	<input type="checkbox"/> FreeStyle Linear Drain™ Drain Flanges Sitting on Substrate
Drain Length: _____	Drain Length: _____
<input type="checkbox"/> Solutions Linear Drain 	<input type="checkbox"/> Custom Base Depth at Drain Base Depth at Drain: _____
Drain Length: _____	Drain Length: _____
<input type="checkbox"/> Check this box to include PBI Cradle for Solutions Linear Drain in shipment	NOTE: Approval by Noble Company is required

NOBLE QUOTE
Sq In Price: (See Distributor Price)
Total Area: (A x B)
Quantity: (How many of this base)
Price Each: (Sq In Price x Total Area)

NOTE: Price is for BASE ONLY; all other items (including drains) are sold separately.
 If "Clamping Ring Drain" is selected for section 4, a NobleFlex Drain Flashing will be included.

3c. PROBASE II CUSTOM SHOWER BASE CUSTOM DIMENSIONS - Unique Shape (Neo-Angle, L-Shaped, etc.)

RECTANGLE OR SQUARE SHAPED BASES MUST BE ENTERED ON THE FRONT SIDE OF THIS FORM (4a or 4b), NOT ON THIS GRAPH

Check this box for Unique-Shaped Base

Draw your Unique Custom Base Shape on the graph to the left and include all base dimensions, including depth (if different from the standard depths).

Incorporate placement, shape, and size of drain, and if planning on using a linear drain, indicate the direction of the slope related to drain.

In the notes section below, indicate drain being used (FreeStyle Thin-Bed Drain, FreeStyle Linear Drain, Solutions Linear Drain, or Other)

Section 1 (contact and shipping information), Section 2 (shower base selection), and Section 4 (drain hole style/selection) still **must be completed** before submission of form.

Notes:

Quantity:

Price by Noble:

4. PROBASE II CUSTOM SHOWER BASE LEAD TIME

72-Hour Lead Time Parameters and Eligibility - (Upon verification of approval and receipt of P.O., your order will ship within 72 hours)

In order to be eligible for Noble Company's 72-Hour Custom Base lead time, the following parameters must be met:

- Base must be NON-waterproofed Multi-Slope™ (Single-Slope bases and Pre-Waterproofed bases are not currently eligible for 72-Hour lead time).
- Unique Configurations must have 5 sides or less
- Base side dimensions cannot exceed 100 inches
- On Multi-Slope bases, drain hole placement can not be less than 10 inches from the edge of the base to the center of the drain hole.
- Order quantity can not exceed 3 bases (Orders of 4 or more are not eligible for 72 hour lead time).

If your base does not meet the above parameters, refer to "Other Lead Time Parameters" section below.

Other Lead Time Parameters

Bases that do NOT fit into the 72-Hour parameters will typically have a lead time between 5 business days and 2 weeks. This includes:

- Pre-Waterproofed Bases
- Single-Slope Bases
- Unique configurations with more than 5 sides
- Base side dimensions that exceed 100 inches,
- On Multi-Slope bases, drain hole placement less than 10 inches from the edge
- Bases not designed for use with a Noble Company drain
- Bases with a non-standard thickness
- Quantity of 4 or more bases