# Noble Benches

## Installation Instructions

www.noblecompany.com

#### 1. PRODUCT & MATERIALS

- 1.1 Noble Benches are made from high density, expanded polystyrene with an acrylic polymer finish. Noble Benches are waterproof and ready to tile. They are lightweight, durable, and are not a food source for fungus and mold.
- 1.2 Other Tools & Materials Needed: Mortar Mix (for leveling), 1/2" x 1/2" Square-Notch trowel, Modified Thin-Set, and 100% Silicone Sealant.

### 2. PREPARATORY WORK

- 2.1 Shower should be waterproofed in accordance with Tile Council of North America (TCNA) guidelines and all applicable codes prior to the installation of the Bench.
- **2.2** Ensure that the walls where the Bench is to be installed are square and plumb.
- 2.3 In order for the Bench to fit the walls, the floor under the Bench must be square to the walls (i.e. leveled/free of slope). Use a mortar mix beneath the Bench for leveling.
- 2.4 Re-check the fit of the Bench with the walls and floor and repeat until the fit is square and level.

#### 3. INSTALLING BENCH

- 3.1 Apply a medium bed, modified thin-set to the walls behind and the floor under the Bench. Use a ½" X ½" Square-Notch trowel.
- 3.2 Slide the Bench into the thin-set, flattening the ridges.
- **3.3** Ensure that there is complete coverage of the thin-set.
- 3.4 Once Bench is installed, use 100% Silicone Sealant to seal all joints where the Bench meets the walls.
- 3.5 Install tile or stone according to TCNA guidelines.

### 4. ATTACHING BENCHES TOGETHER

- **4.1** Dry fit one Bench to the other.
- 4.2 Apply a medium bed, modified thin-set to the walls behind and the floor under the Bench. Use a 1/2" X 1/2" Square-Notch trowel.
- **4.3** Apply thin-set to side of Bench already installed.
- **4.4** Slide the Bench into the thin-set, flattening the ridges.
- **4.5** Ensure that there is complete coverage of the thin-set.
- **4.6** Once Bench is installed, use 100% Silicone Sealant to seal all joints where the Bench meets the walls and where the two benches meet.
- **4.7** Install tile or stone according to TCNA guidelines.

**NOTE:** For any situation not specifically covered, contact Noble Company's Technical Department at 1-800-878-5788 before proceeding. Follow TCNA guidelines.





























