

NobleSealant 250

LOW VOC Sealant and Seamer

www.noblecompany.com



NobleSealant 250

A low VOC product used for seaming and sealing. NobleSealant 250 is a thermosetting elastomeric hybrid polymer that is unaffected by water when cured. This material is a moisture cure product which can allow for flood testing in 30 minutes to 4 hours depending on environmental conditions.

- Low VOCs
- Thermosetting elastomeric hybrid polymer
- Unaffected by exposure to water when cured
- Seam Noble bonded sheet membranes (follow manufacturer's instructions)
- Seal penetrations of the sheet membrane (See Noble Technical Bulletin on patching)
- Fill small cracks, voids, and seams prior to using liquid waterproof membranes (per manufacturer's written instructions)
- Provide seal between waterproof membrane and Noble drain body
- Adhere Thin-Line™ corners and NobleFlex® Drain Flashing to waterproof membrane
- Can be used as sealant around Noble Curbs, Benches, and Niches.

Yield:

10.3 oz tube = 50 lineal feet

5 oz tube = approx 25 lineal feet



Simple Solutions... Proven Performance



VIEW MORE PRODUCT
DETAILS, VIDEOS,
AND DIAGRAMS ONLINE



A division of
FEDERAL PROCESS
CORPORATION

7300 Enterprised Drive, Spring Lake, MI 49456 · (800) 878-5788 · Fax: (231) 799-8850 · www.noblecompany.com
® Registered Trademark of Noble Company ™ Trademark of Noble Company © 2020 Noble Company

File # NS022020-04 | 02/20 Supersedes #NS102019-15