

VIEW MORE PRODUCT  
DETAILS, VIDEOS,  
AND DIAGRAMS ONLINE



# NobleSealant 250

LOW VOC Sealant and Seamer

[www.noblecompany.com](http://www.noblecompany.com)



## NobleSealant 250

*A low VOC product used for seaming and sealing. NobleSealant 250 is a thermosetting elastomeric hybrid polymer that is unaffected by water when cured. This material is a moisture cure product which can allow for flood testing in 30 minutes to 4 hours depending on environmental conditions.*

### BENEFITS

- Low VOCs
- Thermosetting elastomeric hybrid polymer
- Unaffected by exposure to water when cured
- Seam Noble bonded sheet membranes (follow manufacturer's instructions)
- Seal penetrations of the sheet membrane (See Noble Technical Bulletin on patching)
- Fill small cracks, voids, and seams prior to using liquid waterproof membranes (per manufacturer's written instructions)
- Provide seal between waterproof membrane and Noble drain body
- Adhere Thin-Line™ corners and NobleFlex® Drain Flashing to waterproof membrane
- Can be used as sealant around Noble Curbs, Benches and Niches.

#### Yield:

10.3 oz tube = 50 lineal feet

5 oz tube = approx 25 lineal feet



Simple Solutions... Proven Performance



7300 Enterprise Drive, Spring Lake, MI 49456 · 800-878-5788 · Fax: 231-799-8850  
® Registered Trademark of Noble Company, Spring Lake, MI. © 2019 Noble Company  
File # NS102019-15 | 11/19

