

PRESS RELEASE

FOR IMMEDIATE RELEASE

CONTACT: Dave Wormmeester dave@noblecompany.com 800.878.5788

ProBase II®

ProBase II provides a complete solution for a linear drain installation. It installs quickly and easily with modified thin-set to provide the code-required slope to drain in conjunction with Noble Company's Freestyle Linear Drain™. ProBase II is offered in two configurations:

32x60 Tub Replacement Kit

This unit can be used for showers from 30"x30" up to 32"x60" tub replacement and includes all components in a single box – including the linear drain.

Components include: Patent Pending composite base pieces and shim pieces to accommodate a 32x60 tub replacement, with shims that will offset the drain up to 4 1/2" from the wall and center the drain within the width opening; (1) 3'x44' roll of ValueSeal® waterproofing sheet membrane; Freestyle Linear Drain (user selected – base material, drain width, and strainer style); (2) 30" Solid Curbs; (4) Thin-Line™ Inside Corners, (4) Thin-Line Outside Corners, (1) Thin-Line Mixing Valve Collar and (1) Thin-Line Pipe Collar along with a tube of NobleSealant.

64x64 Base Kit with Accessory Kit

This unit can be used for showers from 32"x33" up to 64"x64" and includes all components in two boxes – including the linear drain.

Components in Box 1 include: Patent Pending composite base pieces and shim pieces to accommodate from 32"x32" base to 64"x64" base, with shims that will offset the drain up to 4 1/2" from the wall and center the drain within the width opening.

Components in Box 2 include: (1) 3'x44' roll of ValueSeal waterproofing sheet membrane; (1) 6'x9' section of ValueSeal waterproofing for the base of the shower (to allow for a one-piece pan with no seams); Freestyle Linear Drain (user selected – base material, drain width, and strainer style); (1) 72" Solid Curb; (4) Thin-Line Inside Corners, (4) Thin-Line Outside Corners, (1) Thin-Line Mixing Valve Collar and (1) Thin-Line Pipe Collar along with a tube of NobleSealant.



ProBase II Features:

- o Single-slope to drain
- o Superior impact resistance with Patent Pending composite base
- o Sloped honevcomb and foam composite base
- o Noble waterproofing sheet membrane bonds directly to base
- o Two-piece base construction with low profile
- o Allows for ADA configurations
- o Offset or flush-to-wall configuration of drain
- o Ideal integration with FreeStyle Linear Drain
- o Shims included to accommodate off-set drains, can be easily cut to select off-set distance from wall
- o Base is easy to cut to accommodate various shower installations
- o Install with NobleBond EXT of modified thin-set
- o No substrate modification required
- o Customizable for large projects
- o Can be used with all Noble sheet membranes including NobleSeal® TS

Custom ProBase II bases are available for quantity orders. ProBase II is made by Noble Company in America. Visit www.noblecompany.com or call 800-878-5788 for more information about the latest innovations in shower waterproofing.

###

Founded in 1946, the Noble Company has established a reputation of providing quality, innovative products for the plumbing and tile industries. Identifying problems and developing solutions that add value and exceed customer expectations has been the ongoing mission of our company. Noble Company products are available globally through our distribution network.

For over 40 years, Noble Company has pioneered the use of sheet membranes in the tile and stone industry. At the heart of all Noble systems is a core layer of Chlorinated Polyethylene (CPE), an inherently flexible elastomeric sheet that will not rot, crack, or deteriorate due to microorganisms. Sheet membranes are available for crack isolation, waterproofing, joint bridging, and sound reduction. NobleSeal sheets save time and money. Noble membranes are easy to install and provide quality solutions to prevent costly failures. All Noble membranes are made in the U.S.A.

For more information about any Noble Company product, visit our website at www.noblecompany.com, or contact us at 800-878-5788.



