

IAPMO RESEARCH AND TESTING, INC.

5001 East Philadelphia Street, Ontario, California 91761-2816 – USA • 909-472-4100 • 909-472-4244 • www.iapmort.org



CERTIFICATE OF LISTING

IAPMO Research and Testing, Inc. is a product certification body which tests and inspects samples taken from the supplier's stock or from the market or a combination of both to verify compliance to the requirements of applicable codes and standards. This activity is coupled with periodic surveillance of the supplier's factory and warehouses as well as the assessment of the supplier's Quality Assurance System. This listing is subject to the conditions set forth in the characteristics below and is not to be construed as any recommendation, assurance or guarantee by IAPMO Research and Testing, Inc. of the product acceptance by Authorities Having Jurisdiction.

The most updated information on this Certificate of Listing is available online at pld.iapmo.org

Effective Date: November 2018

Void After: November 2019

Product: Shower Pan Liner

File No. 4339

Issued To: Noble Company
7300 Enterprise Drive
Spring Lake, MI 49456

Identification: Manufacturer's name or trademark, and the UPC® certification mark.

Characteristics: Load bearing, bonded, waterproof membranes for thin-set ceramic tile and dimension stone installation. To be installed in accordance with the manufacturers instruction and the latest Uniform Plumbing Code.

Products listed on this certificate have been tested by an IAPMO R&T recognized laboratory. This recognition has been granted based upon the laboratory's compliance to the applicable requirements of ISO/IEC 17025.

Products are in compliance with the following code(s):

Uniform Plumbing Code (UPC®)

Products are in compliance with the following standard(s):

ANSI A118.10-2014


Chairman, Product Certification Committee


CEO, The IAPMO Group



This listing period is based upon the last date of the month indicated on the Effective Date and Void After Date shown above. Any change in material, manufacturing process, marking or design without having first obtained the approval of the Product Certification Committee, or any evidence of non-compliance with applicable codes and standards or of inferior workmanship, may be deemed sufficient cause for revocation of this listing. Production of or reference to this form for advertising purposes may be made only by specific written permission of IAPMO Research and Testing, Inc. Any alteration of this certificate could be grounds for revocation of the listing. This document shall be reproduced in its entirety.



IAPMO RESEARCH AND TESTING, INC.

CERTIFICATE OF LISTING

Void After: November 2019

Product: Shower Pan Liner

File No. 4339

Issued To: Noble Company

MODELS:

NobleSeal® TS

<u>Model No.</u>	<u>Description</u>
Noble Deck™	Composite Sheet of CPE w/Non-Woven Polyester Laminated to Both Sides, .040" mil Thickness (Charcoal)
NobleFlex®	Drain Flashing, Composite Sheet of CPE and Non-Woven Polyester, .040" mil Thickness (Gray) Depths: ½ to 4"
NobleSeal® CIS	Composite Sheet of CPE w/Non-Woven Polyester Laminated to Both Sides, .030" mil Thickness (Blue)
NobleSeal® SIS	Composite Sheet of CPE w/Non-Woven Polyester Laminated to Both Sides, .050" mil Thickness (Green)
NobleSeal® TS	Composite Sheet of CPE w/Non-Woven Polyester Laminated to Both Sides, .030" mil Thickness (Blue)
ValueSeal™	Composite Sheet made from PE w/ Non-Woven Polyester laminated to both sides, .016 mil thickness



IAPMO RESEARCH AND TESTING, INC.

CERTIFICATE OF LISTING

Void After: November 2019

Product: Shower Pan Liner

File No. 4339

Issued To: Noble Company

ADDITIONAL COMPANY INFO:

Dal-Tile Corporation

<u>Model No.</u>	<u>Description</u>
Dal-Seal CIS	Composite Sheet of CPE w/Non-Woven Polyester Laminated to Both Sides, .030" mil Thickness (Orange)
Dal-Sound	Composite Sheet of CPE w/Non-Woven Polyester Laminated to Both Sides, .050" mil Thickness (Maroon)
Dal-Seal TS	Composite Sheet of CPE w/Non-Woven Polyester Laminated to Both Sides, .030" Mil Thickness (Orange)
Dal-Deck™	Composite Sheet of CPE w/Non-Woven Polyester Laminated to Both Sides, .040" mil Thickness (Charcoal)